PANEL H

LOCATION: DELI/BAKERY CORR | SERVES: REFRIG CASE | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 14,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 250 A | BUS: 250A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS | FEED THRU LUGS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
		1	SPACE											
	C	3	PRODUCE CASE 35 F	1	15	200	110		15	1	F JUICE CASE 38	2	C	
	A	5	PRODUCE CASE 35 L	1	20		280	170	20	1	L JUICE CASE 38	4	A	
	A	7	PRODUCE CASE 36 L	1	20	280						6		
	C	9	PRODUCE CASE 36 F	1	15	250	200		15	1	F DELI COUNTER 40	8	C	
	A	11	DELI CASE 39 L	1	20		440	90	20	1	L DELI COUNTER 40	10	A	
	C	13	DELI CASE 39 F	1	15	60		230	20	1	H DELI COUNTER 40	12	C	
	C	15	DELI CASE 39 H	1	20	30	90		15	1	F FLORAL CASE 33	14	C	
	C	17	BAKERY FREEZER 45 L1	39 H	1	15		30	270	20	1	F FLORAL CASE 66	16	C
	C	19	FRZN BAKERY CASE	68 F	1	20	40		180	20	1	CASE RECPTACLE	18	F
	A	21	FRZN BAKERY CASE	68 L	1	20	270	50		15	1	L BAKERY COOLER 44	20	A
	C	23	FRZN BAKERY CASE	68 H	1	20		310	410	15	2	F PRODUCE COOLER 34	22	C
	C	25	DELI COOLER	41 F	2	15	210	310	-	-	F	24	C	
	A	27	DELI COOLER	41 F	-	-	540	210		20	1	L PRODUCE COOLER 34	26	A
	A	29	DELI COOLER	41 L	1	20		210	270	15	2	F DELI COOLER 42	28	C
	A	31	BAKERY FREEZER	43 L	1	20	270	210	-	-	F	42	30	C
	C	33	BAKERY COOLER	44 F	2	15	270	210		20	1	L DELI COOLER 42	32	A
	-	35		44 F	-	-		310	210	15	1	F SALAD CASE 37	34	C
	C	37	DELI SLICNC H-20	47 H	1	20	90		450	20	1	L SALAD CASE 37	36	A
	C	39	DELI SLICNC H-17	47 F	1	20	1884	190		20	1	BOARS HEAD TWIST LOCK	38	E 11
	A	41	DELI SLICND	47 L	1	20		1884	156	130	15	1 BOARS HEAD OUTLET	40	E 11
									130	20	1 L DELI ISLAND	46	42	A
			CONNECTED VA:			4394	2796	3060			DEMAND FACTOR: 1.09			
			TOTAL CONNECTED VA: 10250			AMPS: 28					TOTAL DEMAND AMPS: 31			

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	3640	1.25	4550
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	4390	1.00	4390
D	KITCHEN	0	0.90	0
E	MISC. EQUIPMENT	2040	1.00	2040
F	RECPTS (1st 10 KW)	180	1.00	180
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	10250	1.09	11160

PANEL J

LOCATION: DELI/CORRIDOR | SERVES: DELI/BAKERY | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 42,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 250 A | BUS: 250A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
6		1	SPARE	1	40									
6		3	SPARE	1	40				60	1	SPARE	2		6
6		5	SPARE	1	40				60	1	SPARE	4		6
6		7	SPARE	1	40				60	1	SPARE	6		6
6		9	SPARE	1	40				60	1	SPARE	8		6
6		11	SPARE	1	40				60	1	SPARE	10		6
6		13	SPARE	1	40				60	1	SPARE	12		6
6		15	SPARE	1	40				60	1	SPARE	14		6
	A	17	PRODUCE SIGNAGE LIGHTING	1	20			60	60	1	SPARE	16		6
	A	19	DELI & BAKERY SIGNAGE LIGHTING	1	20	110		260	15	1	F SANDWICH CASE 121	18	C	
		21	SPACE			90			20	1	L SANDWICH CASE 121	20	C	
		23									SPACE	22		
		25										24		
		27										26		
		29										28		
		31										30		
		33										32		
		35										34		
		37										36		
		39										38		
		41										40		
												42		
			CONNECTED VA:			200	0	320			DEMAND FACTOR: 1.08			
			TOTAL CONNECTED VA: 520			AMPS: 1					TOTAL DEMAND AMPS: 2			

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	170	1.25	213
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	350	1.00	350
D	KITCHEN	0	0.65	0
E	MISC. EQUIPMENT	0	1.00	0
F	RECPTS (1st 10 KW)	0	1.00	0
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	520	1.08	563

PANEL K

LOCATION: DELI/BAKERY CORR | SERVES: DELI | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 10,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 250 A | BUS: 250A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
	A	1	LIGHTING	1	20	1920								
11	C	3	03UMA-4 CASE	1	20	180	1548		20	1	DELI APMG	2	F	9
9	F	5	DELI BEVERAGE CENTER	1	20		840	360	20	1	DELI/BAKERY OFFICE RECPT	4	F	
	F	7	RECEPTACLE	1	20	180		540	20	1	RECEPTACLE	6	F	
	F	9	RECEPTACLE	1	20	540	180		20	1	RECEPTACLE	8	F	
6	D	11	SPARE	2	20		1200		20	1	3-DOOR REFRIGATOR	10	E	
6		13						660	20	1	DELI SLICER	12	D	9
	A	15	DELI LIGHTING	1	20	660	840		20	1	DELI SLICER	14	D	9
	A	17	DELI LIGHTING	1	20		660	840	20	1	DELI SLICER	16	D	9
	A	19	DELI LIGHTING	1	20	840		1822	30	2	DELI HOT CASE (DPBHP60WD) <G>	18	D	2
3	D	21	DELI HOT CASE (GHSS476HRD) <G>	2	40	1822	2695					20	L	2
3	-	23		-	-		1200	2695	20	1	DELI SOUP BAR <G>	22	E	3
9	D	25	POPCORN MACHINE <G>	1	30	2400		5980	60	3	POT WASHER	24	D	
	A	27	BAKERY LIGHTING	1	20	5980	1050					26	-	
	A	29	BAKERY LIGHTING	1	20		5980	1050	-	-		28	-	
	A	31	BAKERY LIGHTING	1	20	1050		190	20	1	SHUNT TRIP	30	E	
	F	33	RECEPTACLE	1	20	790	800		20	3	DELI HOOD FAN F-S	32	E	9
	F	35	RECEPTACLE	1	20		790	360	-	-		34	-	9
	E	37	FANS F-8,7 & 8	1	20	1180		790	-	-		36	-	9
3	D	39	DELI HOT CASE (GHSS476HRD) <G>	1	15	47	46		15	1	DELI HOT CASE (DPBHP60WD) <G>	38	D	3
2	C	41	BEVERAGE CENTER ICE M/C	1	20		240	1132	20	1	DELI INSECT-O-CUTER	40	E	
								1920	20	1	DELI CORRIDOR LTNG	42	A	
			CONNECTED VA:			17589	18069	18339			DEMAND FACTOR: 0.84			
			TOTAL CONNECTED VA: 53997			AMPS: 150					TOTAL DEMAND AMPS: 126			

<G> PROVIDE GFCI BREAKER

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	9510	1.25	11888
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	2680	1.00	2680
D	KITCHEN	31447	0.65	20441
E	MISC. EQUIPMENT	6380	1.00	6380
F	RECPTS (1st 10 KW)	3980	1.00	3980
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	53997	0.84	45368

PANEL L

LOCATION: DELI CORR | SERVES: DELI/COOKING | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 10,000 A | PANEL TYPE: S1 | MCB 225A <1> | BUS: 250A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS | 120 VOLT SHUNT TRIP

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
7,13	D	1	CHESTER FRYER (MGF-72)	3	80	6960								
7,13	-	3		-	-		6960		-	-	SHUNT TRIP	2	-	7,13
7,13	-	5		-	-			6960	80	3	CHESTER FRYER (MGF-72)	4	D	7,13
7,13	D	7	SHUNT TRIP	-	-		6960					6	-	7,13
3,13	-	9	NEW FRYER	3	80	6960	6960		-	-		8	-	7,13
3,13	-	11		-	-			6960			SPACE	10	-	
3,13	D	13		-	-	6960					SPACE	12	-	
3,13	-	15	SHUNT TRIP	-	-				20	1	SPARE	14	-	6
		17	SPACE						20	1	SPARE	16		6
		19	SPACE						20	1	SPARE	18		6
6		21	SPARE	2	30				20	1	SPARE	20		6
6		23		-	-				20	1	SPARE	22		6
7	D	25	HEAT & HOLD <G>	2	40	3006			20	1	SPARE	24		6
7	-	27		-	-		3006		30	1	SPARE	26		6
		29	SPACE						30	1	SPARE	28		6
									20	1	SPARE	30		6
			CONNECTED VA:			23886	23886	20880			DEMAND FACTOR: 0.65			
			TOTAL CONNECTED VA: 68652			AMPS: 191					TOTAL DEMAND AMPS: 124			

<G> PROVIDE GFCI BREAKER

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	0	1.25	0
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	0	1.00	0
D	KITCHEN	68652	0.65	44624
E	MISC. EQUIPMENT	0	1.00	0
F	RECPTS (1st 10 KW)	0	1.00	0
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	68652	0.65	44624

<1> SHUNT TRIP MAIN BREAKER UPON ACTION OF HOOD ANSUL SYSTEM

<2> SHUNT TRIP BRANCH BREAKERS NOTED UPON ACTUALATION OF GFI SENSOR

PANEL NEW L1

LOCATION: DELI CORRIDOR | SERVES: DELI | MOUNT: FLUSH
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 22,000 A | PANEL TYPE: NQOD | MAIN BREAKER: 225 <1> | BUS: 225 A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS | SHUNT TRIP MAIN

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
	D	1	COMBI OVEN (CTP7-20E) <2>	3	60	6400								
	-	3		-	-		6400				SPACE ONLY	2		
	-	5		-	-			6400				4		
	-	7	SHUNT TRIP	-	-							6		
	D	9	COMBI OVEN (CTP7-20E) <2>	3	60		6400					8		
	-	11		-	-			6400				10		
	-	13		-	-	6400						12		
	-	15	SHUNT TRIP	-	-							14		
	-	17	SPACE ONLY									16		
		19										18		
		21										20		
		23										22		
		25										24		
		27										26		
		29										28		
		31										30		
		33										32		
		35										34		
		37										36		
		39										38		
		41										40		
												42		
			CONNECTED VA:			12800	12800	12800			DEMAND FACTOR: 0.65			
			TOTAL CONNECTED VA: 38400			AMPS: 107					TOTAL DEMAND AMPS: 69			

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	0	1.25	0
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	0	1.00	0
D	KITCHEN	38400	0.65	24960
E	MISC. EQUIPMENT	0	1.00	0
F	RECPTS (1st 10 KW)	0	1.00	0
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	38400	0.65	24960

<1> SHUNT TRIP MAIN BREAKER UPON ACTION OF HOOD ANSUL SYSTEM

<2> SHUNT TRIP BRANCH BREAKERS NOTED UPON ACTUALATION OF GFI SENSOR

PANEL M

LOCATION: DELI CORR | SERVES: DELI | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 14,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 250 A | BUS: 250A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS | 120 VOLT SHUNT TRIP

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
		1	SPACE											
6		3	SHUNT TRIP	1	20									
6		5	SPARE	3	50						SPACE	2		
6		7		-	-							4		
6		9		-	-	540			20	1	RECEPTACLE	6	F	
9	D	11	ROUNDER	3	20		1470	1200	20	1	BAKERY FAN SF-1	8		
9	-	13		-	-	1200		1000	20	1	EDF	10	E	
9	-	15		-	-	540	1200		20	1	RECEPTACLE	12	E	
9	D	17	KEMPER SPIRAL MIXER	3	50		1230	2960	30	3	MIXER	14	F	
9	-	19		-	-	2960		1230	-	-		16	D	9
9	-	21		-	-	1230	2960		-	-		18	-	9
3	D	23	DELI BLAST CHILLER	3	30		960	1920	20	3	CUTLER OVEN	20	D	
3	-	25		-	-	1920		960	-	-		22	-	
3	-	27		-	-	960	1920		-	-		24	-	
	D	29	BAKERY RACK OVEN	3	20		4440	530	60	3	BAKERY PROOF BOX	26	D	
	-	31		-	-	530		4440	-	-		28	-	
	-	33		-	-	4440	530		-	-		30	-	
	E	35	BAKERY OVEN CONTROLS F-10	1	20		1200	1570	20	1	BAKERY PROOF BOX CONTROLS	32	-	
	E	37	CUTLER OVEN CONTROLS	1	20	720		500	20	1	DELI HOOD CONTROLPANEL	34	E	
	D	39	WATER CHILLER	1	20	360	30		20	1	PROOF BOX WATER SOFTENER	36	E	9
	E	41	EDF	1	20		990	1000	30	2	WATER CHILLER	38	E	
								990	-	-		40	D	3
												42	-	3
			CONNECTED VA:			15400	16930	18300			DEMAND FACTOR: 0.71			
			TOTAL CONNECTED VA: 50630			AMPS: 141					TOTAL DEMAND AMPS: 100			

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	0	1.25	0
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	0	1.00	0
D	KITCHEN	41730	0.65	27125
E	MISC. EQUIPMENT	7820	1.00	7820
F	RECPTS (1st 10 KW)	1080	1.00	1080
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	50630	0.71	36025

PANEL MA

LOCATION: DELI CORRIDOR | SERVES: BAKERY | MOUNT: SURFACE
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 10,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 125A | BUS: 225 A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
	E	1	DELI 4X4	1	20	1500								
		3	SPARE	1	20	80			20	1	BAKERY DISPLAY	2	F	7,9
		5	SPARE	1	20		80		20	1	BAKERY DISPLAY	4	F	7,9
	D	7	BAKERY MIXER	1	20	700		1170	20	1	BAKERY DISPLAY	6	F	7,9
	D	9	BAKERY REFRIGERATOR (MARBLE TOP)	1	20		1200		20	1	SPARE	8		
	D	11	BAKERY REFRIGERATOR (MARBLE TOP)	1	20		180	1200	20	1	RECEPTACLE	10	F	
	E	13	BAKERY BC 48	1	20	200		1220	20	1	BREAD SLICER	12	D	
7,9	D	15	SHEETER	1	20		1180		20	1	SPARE	14		
7,9	F	17	CORD REEL SEASONAL DISPLAY	1	20		180	1200	20	1	BAKERY CEILING MTD RECPT	16	F	
7,9	F	19	CORD REEL SEASONAL DISPLAY	1	20	1800		170	20	1	SHS2436	18	F	7,9
	D	21	GLAZE TABLE BUG LIGHT S-300	1	20	60	410		20	1	BAKERY SHS 60	20	F	7,9
11	E	23	EXISTING	3	20			1500			SPACE	22		
11	-	25				-	1500	2500	30	2	BAKERY CAKE CASE	24	C	11
11	-	27				-	2500	1500	-	-		26	-	11
11	F	29	CORD REEL SEASONAL DISPLAY	1	20			2500	30	2	BAKERY CAKE CASE	28	C	11
		31	SPACE					2500	-	-		30	-	11
		33	SPACE								SPACE	32		
11	F	35	CORD REEL SEASONAL DISPLAY	1	20			1550			SPACE	34		
		37	SPACE					3006	40	2	DELI HEAT & HOLD <G>	36	D	5
5	D	39	DELI TURBO CHEF <G>	2	30	3006	2496		-	-		38	-	5
5	-	41				-	1000	2496	20	1	DELI WRAPPER <G>	40	D	5
								1920	20	1	DELI HOT CASE (GHS355H) <G>	42	D	5
			CONNECTED VA:			11346	10726	21982			DEMAND FACTOR: 1.00			
			TOTAL CONNECTED VA: 44054			AMPS: 122					TOTAL DEMAND AMPS: 122			

<G> PROVIDE GFCI BREAKER

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	0	1.25	0
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	10000	1.00	10000
D	KITCHEN	19834	1.00	19834
E	MISC. EQUIPMENT	6200	1.00	6200
F	RECPTS (1st 10 KW)	8020	1.00	8020
	(Remaining Recpt.s)	0	0.50	0
	TOTAL DEMAND VA:	44054	1.00	44054

PANEL N

LOCATION: EMPLOYEE LOUNGE | SERVES: FRONT END | MOUNT: FLUSH
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 10,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 250 A | BUS: 250 A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
	A	1	LOUNGE LTG	1	20									
		3	SPARE	1	20	850			20	1	CHECKOUT #2 & MERCH	2	F	9
9	F	5	CHECKOUT #1 & MERCH	1	20		850	850	20	1	CHECKOUT #3 & MERCH	4	F	9
		7	SPARE	1	20			850	20	1	CHECKOUT #4 & MERCH	6	F	9
9	F	9	CHECKOUT #5 & MERCH	1	20	850	850		20	1	SELF CHECKOUT #8A,B & C	8	F	9
9	F	11	CHECKOUT #6 & MERCH	1	20		180	850	20	1	PHARMACY RECPT	10	F	
9	F	13	SELF CHECKOUT #7A,B & C	1	20	850		720	20	1	PLUGMOLD WIREMOLD	12	F	
9	F	15	CHECKOUT #9	1	20	1620	360		20	1	PLUGMOLD WIREMOLD	14	F	
9	E	17	GDM-72 COOLER	1	20		1620	1440	20	1	PLUGMOLD WIREMOLD	16	F	
	E	19	COFFEE MAKER	1	20	1000		640	20	1	PHARMACY LIGHTING	18	A	
	E	21	COKE MACHINE	1	20	1920	1000		20	1	AQUA VEND	20	E	
	E	23	ELECTRIC WATER COOLER	1	20		180	1000	20	1	BP MACHINE (HIGI)	22	F	
	F	25	MANAGER OFFICE RECEPT	1	20	360		1920	20	1	EXISTING	24	E	
	F	27	MANAGER OFFICE RECEPT	1	20	540	540		20	1	RCPT	26	F	
	F	29	SERVICE RECPT ABOVE CEILING	1	20		540	1920	20	1	RCPT	28	F	
	F	31	OFFICE RECPT	1	20	720		1200	20	1	H/C/CART CHARGER	30	E	
	F	33	OFFICE RECPT	1	20	1000	720		20	1	COKE MACHINE	32	E	
	F	35	OFFICE RECPT	1	20		180	720	20	1	COMMON AREA FLR RECPT	34	F	
	F	37	ATM/OUTSIDE RECPT	1	20	720		1000	20	1	INSTACART COOLERS	36	E	
		39	SPARE	1	20	1000			20	1	INSTACART COOLERS	38	E	
	F	41	PHARMACY RECPT	1	20		1000	180	30	1	INSTACART COOLERS	40	E	
								180	20	1	INSTACART POS	42	F	
			CONNECTED VA:			11790	8020	13470			DEMAND FACTOR: 0.88			
			TOTAL CONNECTED VA: 33280			AMPS: 92					TOTAL DEMAND AMPS: 81			

	LOAD TYPE (LT)	CONNECTED	FACTOR	DEMAND
A	LIGHTING	1000	1.25	1250
B	AIR CONDITIONING	0	1.00	0
C	REFRIGERATION	0	1.00	0
D	KITCHEN	0	0.65	0
E	MISC. EQUIPMENT	13480	1.00	13480
F	RECPTS (1st 10 KW)	10000	1.00	10000
	(Remaining Recpt.s)	8800	0.50	4400
	TOTAL DEMAND VA:	33280	0.88	29130

PANEL Q

LOCATION: CORRIDOR #2 | SERVES: STORE FRONT | MOUNT: FLUSH
PNL VOLTAGE: 120/208, 3P, 4W | PNL AIC (RMS): 10,000 A | PANEL TYPE: S1 | MAIN LUG ONLY: 225 A | BUS: 225 A
BOLT- IN BREAKERS | FULL SOLID NEUTRAL BUS | GROUND BUS | FEED THRU LUGS

CKT NOTE	LT	CKT NO	EQUIPMENT SERVED	P	BKR TRIP	CONNECTED VA A	B	C	BKR TRIP	P	EQUIPMENT SERVED	CKT NO	LT	CKT NOTE
	A	1	GONDOLA LIGHTING	1	20	1200								
	A	3	GONDOLA LIGHTING	1	20	1200	1200		20	1	GONDOLA LIGHTING	2	A	
	A	5	GONDOLA LIGHTING	1	20		1200	1200	20	1	GONDOLA LIGHTING	4	A	
	F	7	GONDOLA RECEPTACLE	1	20	900		1200	20	1	GONDOLA LIGHTING	6	A	
	F	9	GONDOLA RECEPTACLE	1	20		720		30	2	SPARE	8	-	
	E	11	END CAP REFRIG	2	30	1730		1730	30	2	END CAP REFRIG	10	E	
	E	13	END CAP REFRIG	2	30	1730	1730		30	2	END CAP REFRIG	12	E	
	-	15	END CAP REFRIG	-	-	1730	1730		-	-	END CAP REFRIG	14	-	
	E	17	END CAP REFRIG	2	30		1730	1730	30	2	END CAP REFRIG	16	E	
	-	19	END CAP REFRIG	-	-	1730		1730	-	-	END CAP REFRIG	18	-	
	E	21	END CAP REFRIG	2	30	960	1730		20	1	IN-LINE REFRIG CONTROLS	20	E	
	-	23	END CAP REFRIG	-	-		990	1730	30	2	IN-LINE REFRIG UNIT	22	E	
	E	25	IN-LINE REFRIG CONTROLS	1	20	960		990	-	-	IN-LINE REFRIG UNIT	24	-	
	E	27	IN-LINE REFRIG UNIT	2	20	960	990		20	1	IN-LINE REFRIG CONTROLS	26	E	
	-	29	IN-LINE REFRIG UNIT	-	-		990	990	20	2	IN-